

Better Pack® 755eSA/755eMA

ELECTRIC WATER-ACTIVATED TAPE DISPENSERS



Productive, Rugged and Flexible

The Better Pack 755eSA and 755eMA are ideal for high volume sealing applications that include heavy, bulky packages. The 755eSA is engineered for 115V and the 755eMA is engineered for 220V. Each machine has three dispensing modes that give packers complete flexibility to choose the function most suitable in each sealing situation. As an added benefit, the Better Pack 755eSA and the 755eMA handle reinforced and non-reinforced tape from 1 inch to 4 inches wide (2.5 cm to 10.2 cm).

Easy to Use

- Choose from three dispensing modes, manual, auto repeat and 1-2-2 (H-pattern)
- User adjustable tape length allows for dispensing up to 100 inches (190 cm) of tape
- Customize dispensing speed in auto-repeat mode by setting a one second up to a thirty second delay
- Side opening cover provides easy tape loading access

Safe, Convenient and Dependable

- Meets or exceeds UL, CE and CSA standards for operator and electrical safety; RoHS compliant*
- Low profile design provides placement flexibility
- Heavy gauge steel frame construction and few moving parts means minimal maintenance
- Low voltage adjustable water heater warms the water, optimizing tape bonding
- Exposed, large 64 ounce (1.9 liters) water bottle provides water level visibility and easy refill

Model #	Electrical Requirements	Preset Tape Length Range	Tape Width	Gum In or Gum Out (Tape)
755eSA	115v	6" - 100"	1" to 4"	Gum In/Gum Out
755eMA	220v	15.24 cm - 254 cm	2.5 cm to 10.2 cm	Gum In/Gum Out

* Certificate Copies Available Upon Request

For the name and location of your local distributor, call (800) 237-9151 or visit www.BetterPackages.com



Better Pack® 755eSA/755eMA



	Model	Specifications
Dimensions	755eSA	21" L x 10.5" W x 9.5" H
	755eMA	53.3 cm x 26.7 cm x 24.1 cm
Shipping Weight	755eSA	42 lbs.
	755eMA	19.05 kg
Maximum Roll Size	755eSA	Up to 600' roll of tape; Up to 7.5" diameter
	755eMA	Up to 182.9 m roll of tape; Up to 19.05 cm diameter
Tape Width	755eSA	1" to 4"
	755eMA	2.54 cm to 10 cm
Dispensing Speed	755eSA	32"/second
	755eMA	81 cm/second
Water Bottle Capacity	755eSA	64 ounces
	755eMA	1.9 liters
Electrical Requirements	755eSA	115V, 60 Hz, 4 Amps
	755eMA	220V, 50 Hz, 2 Amps
Safety Compliance	755eSA 755eMA	Meets or exceeds UL, CE and CSA standards , RoHS compliant
Warranty	755eSA 755eMA	2 years parts and materials, 6 months labor



4 Hershey Drive
 Ansonia, CT 06401
 Toll Free in US: (800) 237-9151
 P: (203) 926-3700
 F: (203) 926-3705
 E: info@betterpackages.com