



MACHINE APPLIED STRETCH FILM

SuperFLEX[®] **ULTRA & HIGH PERFORMANCE**
brand performance stretch wrap

G7

- Highest available load containment using common pre-stretch levels
- Lowest film weight to load retention ratio in the industry
- Extreme tear resistance - 23% increase over the competition
- Sustainable through plastic use reduction, store drop-off recycling, Cradle to Cradle Certified[®] Silver
- Remarkable clarity with a high gloss finish
 - Produced in 41, 45, & 48 gauges
 - Metric widths only; 500mm & 750mm
 - Available in 2 different roll diameters

GENESYS[®] ULTRA

- High performance stretch film for demanding previous heavier gauge applications
- Offers high pre-stretch levels with adjustable load containment for a variety of demanding applications
- Manufactured on state of the art cast extrusion lines
- High clarity and cling
 - Produced in gauges from 39 to 50
 - Standard widths include 20" & 30"
 - Roll diameters from 8 to 10"

GENESYS[®]

- High performance stretch film for high performance applications
- Offers high load containment
- Excellent puncture / tear resistance
- High cling / slip all while stretching on high speed stretch wrappers at pre-stretch levels up to 300% and beyond
- High clarity and cling
 - Produced in gauges from 50 up to 95.
 - Standard widths are 20" & 30"
 - Roll diameters from 8 to 10"

StretchFLEX[®] **STANDARD PERFORMANCE**
brand stretch wrap

SF1

- Machine cast film designed for a variety of machine film applications
- SF1 has high pre-stretch while preventing breaks during the wrap cycle and spills during transportation
- Differential cling for reduced ability for load sticking together
- High quality cast film
 - Available in gauges from 50 to 120
 - Standard widths are 20" & 30"
 - Roll diameters from 8" to 10"

SSC

- Machine cast film designed for applications needing more cling and slip to protect the load
- SSC has long term success in working in a variety of tough application due to load configurations or equipment limitations
- High quality cast film
 - Available in gauges from 50 to 120
 - Standard widths are 20" & 30"
 - Roll diameters from 8" to 10"

SF3

- Tough biaxially oriented blown film for applications requiring excellent cling and puncture resistance
- SF3 is a standard high performance blown film for customers who expect aggressive cling and improved puncture for their demanding loads
- High quality blown film
 - Available in gauges from 50 to 110
 - Standard widths are 20" & 30"
 - Roll diameters from 8" to 10"

