

4560

7.0 MIL RUBBER THERMOSET ACETATE CLOTH TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

Acetate cloth backing with a thermosetting rubber adhesive system. This product offers high adhesion, conformability, printability, excellent insulating properties and is hand tearable.

PRODUCT APPLICATIONS

Coil wrapping, interlayer insulation, and tabbing. Will accept varnish impregnation.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Acetate Cloth
Backing Thickness	6.0 mil (0.152 mm)
Adhesive	Rubber Thermosetting
Color	White
Total Thickness	7.0 mil (0.178 mm)
Dielectric Strength	2000 Volts
Temp/Class	130°C / B
Insulation Resistance	10 ⁴ megohms
Tensile Strength	40 lbs/in (70 N/cm)
Adhesion to Steel	50 oz/in (5.5 N/cm)
Elongation	15%
Electrolytic Corrosion	1.0 Direct / A, 1*
Flammability	BU 1
Storage Stability	Good
Solvent Resistance	Very Good
Moisture Resistance	Very Good
UL File #	E20780

*VDE 0340



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 10/19

