

# ALF201L-UL

## 2 MIL UL181A-P / B-FX PREMIUM ALUMINUM FOIL TAPE

### DESCRIPTION

ALF201L-UL is engineered and designed to meet UL181A-P and UL181B-FX. (printed for easy identification / inspection). Uses include general purpose seaming, patching and sealing of rigid fiber air duct and connector closure systems to enhance appearance and maintain vapor barrier integrity. The aggressive acrylic pressure-sensitive adhesive provides long-lasting adhesion to clean/dry surfaces. Flame retardant, high shear adhesion, UV and mold resistant. Excellent reflective properties (i.e. heat, light). Superior bonding when exposed to either sub-zero or elevated temperatures. Release coated kraft liner.

### PRODUCT APPLICATIONS

HVAC (Heating, Ventilation and Air Conditioning) duct wrap. For use in Industrial, Appliance, Marine and Aerospace industries. Can be used as protective mask during chemical stripping of metals / other surfaces.

### GOVERNMENT COMPLIANCE

UL Listed: UL181A-P and UL181B-FX



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warranties or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 11/13

## INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b> ASTM C-1136	2 mil (50µ) Aluminum Foil
<b>Adhesive</b>	Acrylic
<b>Tensile Strength</b> (lbs/in width) ASTM D-3759	25 (109 N/25mm)
<b>Elongation</b> (% at break) ASTM D-3759	6
<b>Adhesion to Steel</b> (oz/in) ASTM D-3330	60 (16.4N/25mm)
<b>Adhesion to Backing</b> (oz/in) ASTM D-3330	50 (13.7N/25mm)
<b>Total Thickness w/o liner</b> (mil) ASTM D-3652	4.0 (0.101 mm)
<b>Flame Spread</b> ASTM E-84 / UL-723	0
<b>Smoke Developed</b> ASTM E-84 / UL-723	0
<b>Operating Temperature Range</b>	-30°F to +350°F (-34°C ~ +176°C)

