




ULTRA HIGH PERFORMANCE MACHINE FILM

Enhance load protection while minimizing your environmental impact. G7 leverages your existing equipment to craft exceptionally durable pallets using the least amount of film required. Thinner gauges reduce waste per skid, minimize roll changes, and lower overall costs all while ensuring your products arrive safely.

MANUFACTURED IN A CERTIFIED ZERO WASTE FACILITY



Reduced gauges




Consistent stretch force application



Remarkable clarity with a high gloss finish



Tear resistance 23% increase over the competition**



Highest load containment using common pre-stretch levels**



Lowest film weight to load retention ratio in the industry**

**Based on G7 field analysis



888-898-7834 | itape.com



G7 PERFORMANCE BEATS THE COMPETITION!

The G7 delivers exceptional performance with reduced plastic usage.

It matches the durability of thicker films and outshines competitors of the same thickness.

CUSTOMER CRITICAL TO QUALITY	COMPETITION	G7
GAUGE	45	45
ULTIMATE STRETCH	365%	400%
TEAR TIME	17.93 secs (32% spread)	22.07 secs (42% spread)
LOAD RETENTION	13.03 lbs	14.56 lbs
MD TESTING (Number of breaks at 280% pre-stretch) TARGET: Less than 2 breaks in the roll	Average 8 breaks/roll in 5,000 ft (in all 8 rolls tested)	Average zero breaks/roll (in all 8 rolls tested)
APPLIED FILM WEIGHT	3.16 oz	2.75 oz (13% lower)
COST (In-Field Testing)	"Baseline"	G7 on an average is estimated to save \$8k to \$37k for customers when it replaces incumbent competitor film
CO ² REDUCTION	"Baseline"	Est 1k - 8k lbs less CO ²

ORDERING INFORMATION

PRODUCT CODE	PRODUCT DESCRIPTION	GAUGE	WIDTH (MM)	FOOTAGE (FT)	ROLL WEIGHT (LBS)	ROLLS/PALLET
G71040500-65	10.4MI G7 500MM x 6500'	41	19.7	6,500	21.00	50
G71040500-10	10.4MI G7 19.7" x 10000'	41	19.7	10,000	32.31	40
G71040750-65	10.4MI G7 29.5" x 6500'	41	29.5	6,500	31.45	25
G71040750-10	10.4MI G7 29.5" x 10000'	41	29.5	10,000	48.38	20
G71140500-65	11.4MI G7 19.7" x 6500'	45	19.7	6,500	23.05	50
G71140750-95	11.4MI G7 19.7" x 9500'	45	19.7	9,500	33.69	40
G71140750-65	11.4MI G7 29.5" x 6500'	45	29.5	6,500	34.52	25
G71140750-95	11.4MI G7 29.5" x 9500'	45	29.5	9,500	50.45	20
G71210500-55	12.1MI G7 19.7" x 5500'	48	19.7	5,500	20.80	50
G71210500-90	12.1MI G7 19.7" x 9000'	48	19.7	9,000	34.04	40
G71210750-55	12.1MI G7 29.5" x 5500'	48	29.5	5,500	31.15	25
G71210750-90	12.1MI G7 29.5" x 9000'	48	29.5	9,000	50.98	20

ENVIRONMENTAL IMPACT CALCULATOR*

This tool aims to help businesses reduce their environmental impact while optimizing their packaging efficiency. By using the calculator, companies can lower their stretch film usage and make more sustainable choices.

Contact your IPG sales representative or by calling our Inside Sales team at **1-888-898-7834** to get started.

*Environmental sustainability calculation methodology validated by third-party sustainability consulting firm, LCA Design.



STRETCH FILM

ipg ENVIRONMENTAL IMPACT CALCULATOR



Scan for more info or visit itape.com/stretch

